

Maksymalny zakres dopuszczalnych ciśnień (w PSI) dla danego modelu kół, danego zastosowania i danej szerokości ogumienia

Model kół	Wersja	Zastosowanie: szosa							Zastosowanie: gravel oraz CX					
		19-20mm	20-22mm	22-24mm	24-26mm	26-28mm	28-30mm	30-32mm	28-30mm (1,1-1,18")	30-32mm (1,18-1,26")	32-34mm (1,26-1,34")	34-36mm (1,34-1,42")	36-39mm (1,42-1,54")	39-42mm (1,54-1,65")
VINCI SL 30T, 46T	Szytka	X	X	33-170	33-170	33-160	33-150	33-150	X	X	X	X	X	X
VINCI TORE 38T, 50T, 60T, 88T	Szytka	X	X	33-170	33-165	33-155	33-150	32-130	X	X	X	X	X	X
VINCI TORE 38C, 50C, 60C, 88C	Opona	X	X	35-130	35-115	35-100	35-85	35-70	X	X	X	X	X	X
VINCI RAPID 40T,56T,86T	Szytka	X	33-170	33-170	33-165	33-155	33-140	32-120	X	X	X	X	X	X
VINCI RAPID 40C,56C,86C	Opona	X	35-130	35-130	35-115	35-100	35-85	35-70	X	X	X	X	X	X
VINCI XDR Rim i Disc 38T, 51T	Szytka	X	X	33-170	33-170	33-160	30-160	28-150	30-130	28-130	25-120	25-110	25-100	25-100
VINCI XDR Rim i Disc 38C, 51C	Opona	X	X	35-130	33-120	32-115	30-110	28-100	30-90	28-85	25-85	25-80	25-75	25-75
VINCI CX1 30T	Szytka	X	X	32-150	32-150	32-150	30-150	27-140	30-130	27-120	23-120	23-110	23-100	23-100
VINCI CX1 28C	Opona	X	X	X	X	32-90	30-85	27-85	30-75	27-75	24-70	24-65	24-60	24-55

Model kół	Wersja	Zastosowanie: CX oraz MTB						
		1,65-1,75" (42-44,5mm)	1,75-1,9" (44,5-48mm)	1,9-2,05" (48-52mm)	2,05-2,2" (52-56mm)	2,2-2,4" (56-61mm)	2,4-2,6" (61mm-66mm)	2,6-2,75" (66-70mm)
VINCI CX1 30T	Szytka	X	X	X	X	X	X	X
VINCI CX1 28C	Opona	24-50	24-45	23-45	22-45	X	X	X
VINCI ARMA	Opona	25-41	25-41	23-41	22-40	22-39	X	X
VINCI SCUDO	Opona	X	25-41	23-41	22-40	22-39	22-38	X
VINCI LARGO	Opona	X	X	X	22-41	22-40	22-39	21-37